



SLENERGY

SL-BH High Voltage Battery System

SL-BH series is a high voltage battery that offers multiple energy storage options through an expandable modular design (3-8 modules combined), which further simplifies installation and O&M with multiple smart functions. The safest battery cell technology (LiFePO₄) comes with a high charging rate, ensuring superior performance.



Original battery active balance technology



Flexible capacity options,
7.68kWh to 20.48kWh



Easy installation with
modular and stacked design



Remote diagnosis
and real-time data monitoring

	SL-BH-3-7	SL-BH-4-10	SL-BH-5-12	SL-BH-6-15	SL-BH-7-17	SL-BH-8-20
Electrical Parameters						
NO. of series battery	3	4	5	6	7	8
Rated energy (kWh)	7.68	10.24	12.8	15.36	17.92	20.48
Usable energy (kWh)	6.9	9.2	11.52	13.8	16.13	18.4
Rated voltage (V)	153.6	204.8	256	307.2	358.4	409.6
Voltage range (V)	134.4~172.8	179.2~230.4	224~288	268.8~345.6	313.6~403.2	358.4~460.8
Rated capacity (Ah)	50					
Charge current (A)	25(Recommended)/50(MAX)					
Discharge current (A)	25(Recommended)/50(MAX)					
Cycle times	80% DOD, cycles>6000, residual capacity>70%					
Communication	RS485/RS232/CAN 2.0					
Protection function	Over voltage / Under voltage / Over temperature / Low temperature / Over current / Short circuit					
Size (W×D×H, mm)	710×320×639	710×320×776	710×320×913	710×320×1050	710×320×1187	710×320×1324
Weight (kg)	118	150.8	183.6	216.4	249.2	282
Working Conditions						
Installation	Indoor					
Working temperature	-10°C~50°C					
Optimum working temperature	20°C~30°C					
Storage temperature	-30°C~60°C					
Protection degree	IP54					
Humidity	5%~95%					
Altitude (m)	< 2000					
Cooling	Natural					
Certificate	CE, UN38.3, MSDS, CB/EMC, IP					

